

Tandberg LTO Full Height Drive

Leading Performance and Capacity

LTO Ultrium is the industry standard mid-range tape drive technology on the market today. The Ultrium LTO format has quickly become the market leader overtaking other proprietary technologies such as DLT and AIT.

The availability of four generations of LTO tape drives simplifies the decision—it is the only affordable option available for requirements where capacity growth potential matches the escalating data growth rates that businesses are facing today.

Increasing attention is being paid to the need to protect company data against theft or accidental loss, particularly data that contains personal or sensitive information of a company's customers. The Tandberg LTO-4 SAS and Fibre Channel drives include data encryption capabilities within the drive, helping to avoid the need for host-based encryption of data or the use of specialized encryption appliances. This will provide customers with great ability to protect information if cartridges are lost or stolen.

The fourth generation of Tandberg LTO drives are designed to meet the storage challenges faced by organizations today. Exponential data growth, couple with business continuity requirements, regulatory compliance and resource constraints make the need for reliable, cost effective data production solution more necessary than ever before. The Tandberg LTO drives address these requirements by offering capacities up to 1.6TB*, high-throughput and enterprise class features.

LTO



Key Benefits

- Performance**
 LTO drives are the fastest midrange drive in the industry with transfer speeds up to 240 MB/s*
- Low Total Cost of Ownership (TCO)**
 Compatibility with previous generations of LTO media for investment protection and high capacity results in lower TCO
- High Capacity**
 With capacities up to 800GB native today, the LTO roadmap offers a six-generation migration path with capacities up to 3.2TB*
- Reliability**
 Rock-solid reliability and data integrity with MTBF of 250,000 hrs at 100% duty cycle
- Digital Speed Matching (DSM)**
 DSM is designed to improve throughput in environments where the host data rates vary
- Write Once, Read Many (WORM)**
 WORM allows you to store data in a non-erasable, non-amendable format
- Minimize Downtime**
 3-year warranty and 3 years of Advanced Replacement Service**



Choose between LTO-3 and LTO-4 technology, with native capacities of 800 and 1600GB, high performance and backward read and write compatibility

TANDBERG DATA 
Securing your Information

Specifications

	Tandberg LTO-3 FH	Tandberg LTO-4 FH
Capacity (native/compr.)	400GB / 800GB	800GB / 1600GB*
Transfer Rate (native/compr.)	80MB/s / 160MB/s	120MB/s / 240MB/s
Interface	HD LVD Ultra 160 SCSI	4GB FC, 3GB SAS, HD LVD Ultra 160 SCSI
Number of Tracks	704	824
Buffer Size	128MB	256MB
Data Cartridge	LTO-3	LTO-4
Write	LTO-3, LTO-2	LTO-4, LTO-3
Read	LTO-3, LTO-2, LTO-1	LTO-4, LTO-3, LTO-2
Data Rate Matching	Digital speed matching (DSM) from 40MB/s to 80MB/s	DSM from 30MB/s to 120MB/s
Average Rewind Time	55s	54s
Encoding/Decoding	PRML	PRML
MTBF	250,000 hrs @ 100% duty cycle	
Error Rate (calculated)	1x10 ¹⁷ Bytes per permanent read error	
Error Rate (validated)	1x10 ¹⁴ Bytes per permanent read error	
Error Rate (validated)	1x10 ¹³ Bytes per permanent read error	
Temperature	50F to 100F (10C to 40C) Operating	
Relative Humidity	20 to 80% (non-condensing)	
Electrical Power	5V at 3.3 A, 12 V at 1.1 A (steady state)	
Power Specification	100-240 VAC	
Supported Systems	Microsoft® Windows 2004; Microsoft Windows Server 2003; Sun Solaris 8,9; HP-UX 11.0, 11i; Linux® (Red Hat Enterprise Server 3, SUSE LINUX Enterprise Server 8; AIX® Version 5L 5.1, 5.2, 5.3; and Novell NetWare)	OS400, AIX 5.1 or above, Solaris, HPUX, Netware, Windows 2003, Linux (Generic and Redhat)
Warranty (Internal/External)	3 years and 3 years Advanced Replacement Service**	

* Assumes a 2:1 compression ratio

** Availability dependent on location

Form Factor	(internal)	(external)
Height:	8.5cm (3.33 in)	14.6cm (5.75 in)
Width:	14.9cm (5.83 in)	17.1cm (6.74 in)
Length:	21.1cm (8.33 in)	33.3cm (13.11 in)
Weight:	3.0kg (6.6 lbs)	6.6kg (4.3 lbs)

About Tandberg Data

Tandberg Data is a leading global supplier of backup and archiving technologies. Tandberg Data offers a complete range of tape libraries, tape autoloaders and tape drives (based on the LTO™, SLR™, VXA® tape technology platforms), storage software, data media and disk-based storage such as the RDX™ QuikStor. These solutions are marketed exclusively through a channel of qualified resellers and distributors. These solutions are underpinned by OEM agreements with major server manufacturers including IBM, Hitachi, Fujitsu, Fujitsu-Siemens, Apple and Dell and supported by all major operating systems and storage software applications to operate in heterogeneous network environments. All solutions are designed to meet the growing storage requirements of small and medium-sized organisations with scalability, reliability and backward compatibility features that ensure cost effective operation and long-term investment protection.

Tandberg Data ASA
Økernveien 94
N-0579 Oslo
Norway
Tel: +47 (0) 2218 9090
Fax: +47 (0) 2218 9550

Tandberg Data GmbH
Feldstrasse 81
44141 Dortmund
Germany
Tel: +49 (0) 231 5436 - 0
Fax: +49 (0) 231 5436 - 111

Tandberg Data Limited
Bloxxham Mill Business Centre
Barford Road, Bloxxham
Banbury, England, OX15 4FF
Tel: +44 (0) 845 070 6916
Fax: +44 (0) 1295 722 109

Tandberg Data S.A.S.
16-18, avenue Morane Saulnier - Bât.A
78941 Vélizy Cedex
France
Téléphone: +33 (0)1 39 26 01 01
Télécopie: +33 (0)1 34 65 02 89

Tandberg Data Corporation
2108 55th Street
Boulder, CO 80301
USA
Tel: 303.442.4333
Fax: 303.417.7170

Tandberg Data (Asia) Pte Ltd
20 Bendemeer Road
#04-05 Cyberhub
Singapore 339914
Tel: +65 (0) 6396 0786
Fax: +65 (0) 6396 0787

In addition to the offices above TANDBERG DATA ASA has branch offices in the United Kingdom, France, Italy, India, China (PRC), Thailand and Brazil. TANDBERG DATA ASA is a publicly held company based in Oslo, Norway and is traded on the Oslo Stock Exchange (ticker=TAD). Specifications subject to change without notice. RDX QuikStor, BAKStor, and SLR are trademarks of Tandberg Data ASA. RDX is a registered trademark of ProStor Systems. LTO is a trademark of HP, IBM and Quantum. All other trademarks are the property of their respective owners. ©2007 TANDBERG DATA. All rights reserved.

DS-3FH_EMEA_2007